


## Z-Drive PCI Express Storage Solutions



## Z-Drive R4 C Series Solid State Drives

### C Series at a Glance

- Innovative storage system that melds hardware & software managed solutions with integrated proprietary technology
- Cost-effective MLC-based design with best-in-class endurance
- Advanced feature-set includes user-selectable data recovery & non-stop modes
- Available in half height and full height configurations

### The Pinnacle of Storage Performance

- Delivers the performance of thousands of hard disk drives in a single server
- Eliminates I/O and bandwidth bottlenecks
  - Up to 2,800 MB/s and 500,000 IOPS (per SuperScale controller)

### Proprietary Virtualized Controller Architecture™ (VCA) 2.0

- Multifaceted virtualization layer that interfaces with host system
- Enables TRIM, SCSI unmap, & SMART monitoring for system administrators

### SuperScale™ Storage Accelerator Unique to OCZ

- Facilitates scalable performance in enterprise & datacenter applications
- Unique complex command queuing structure plus queue balancing algorithms
- Provides highly efficient performance aggregation while reducing the burden on host resources

### Superior Reliability, Endurance, & Security Features

- Data fail recovery ensures superior reliability
- Intelligent block management & wear-leveling for increased endurance
- Advanced security with 256-bit AES encryption support
- Strong error correction for enhanced data integrity

### KEY DIFFERENTIATORS:

- Highest performing enterprise PCIe solution on the market
- Merges the best features of pure hardware and software based approaches to data management and overcomes the inherent weaknesses of both
- Bootable as a direct-attach device
- Ultra-high endurance for enterprise applications (increases drive life by up to five times the rated P/E cycles of the NAND)
- Lowest CPU and memory resource utilization in its class
- Only PCIe drive with complete power fail protection & drive-level recovery (R Series)
- Maintains user-configurable flexibility not found in other enterprise storage devices
- Only virtualization layer in the industry with TRIM and SCSI unmap support



PHYSICAL	CM84 Version	CM88 Version
Usable Capacities (IDEMA)	300GB, 600GB, 1.2TB	800GB, 1.6TB, 3.2TB
NAND Components	Multi-Level Cell (MLC)	Multi-Level Cell (MLC)
Interface	PCI Express Gen. 2 x8	PCI Express Gen. 2 x8
Form Factor	PCIe half height, half length compliant	PCIe full height, ¾ length compliant
Storage Controller	OCZ SuperScale™	OCZ SuperScale™
NAND Controller	SandForce® 2281 x 4	SandForce® 2281 x 8
Dimensions (L x W x H)	168.55 x 68.91 x 17.14 mm	242 x 98.4 x 17.14 mm
Weight	119g	262g
PERFORMANCE		
Max Read	up to 2,000 MB/s	up to 2,800 MB/s
Max Write	up to 2,000 MB/s	up to 2,800 MB/s
Random Write Operations (4kB)	250,000 IOPS	410,000 IOPS
Random Write Operations (8kB)	160,000 IOPS	275,000 IOPS
Maximum IOPS	260,000 IOPS	500,000 IOPS
ENVIRONMENTAL		
Power Consumption	Idle: 14.5 W Active: 16 W	Idle: 23 W Active: 26 W
Operating Temperature	0°C ~ 70°C	0°C ~ 70°C
Storage Temperature	-45°C ~ 85°C	-45°C ~ 85°C
Airflow Requirement	100 Linear Feet/Minute (LFM)	100 Linear Feet/Minute (LFM)
Certifications	RoHS, CE, FCC	RoHS, CE, FCC
RELIABILITY/SECURITY		
Data Fail Recovery	Recovers data from up to one NAND flash block per NAND controller	
Data Path Protection	ECC: Up to 55 bits correctable per 512-byte sector; Data path parity protection	
Data Reliability	Read Unrecoverable Bit Error Rate (UBER) 10e-16	
Data Encryption	128-bit & 256-bit AES-compliant	
Product Health Monitoring	SMART support	
COMPATIBILITY		
PCI Express	PCI Express x8 or x16 slot; Fully compliant with the PCI Express Electromechanical Specification Rev. 2.0, and PCI Express Base Specification Rev. 2.0	
Operating Systems	Windows 7 32-bit/64-bit; Windows Server 2003 & 2008 R2 64-bit; Red Hat Enterprise Linux, CentOS, Oracle Enterprise Linux, SUSE Linux Enterprise Server, Ubuntu Server and Desktop	
Power Requirements	PCI Express 12V & 3.3V	
ADDITIONAL FEATURES		
Flash Virtualization Layer	OCZ VCA (Virtualized Controller Architecture™) 2.0	
Performance Optimization	TRIM/SCSI unmap (requires OS support)	
Service & Support	3-Year Warranty; Dedicated FAE/FSE support (includes PM/engineer support through validation cycle)	




## Dramatically Accelerating Enterprise Applications

The OCZ Z-Drive R4 Series represents a turning point in the evolution of PCIe attached solid state storage by merging the best feature sets of both the pure hardware and pure software based approaches to data management. Designed and manufactured for a wide range of enterprise environments including cloud computing and data centers, the Z-Drive R4 features OCZ's Virtualized Controller Architecture (VCA) 2.0, providing the utmost in performance, flexibility, durability and enhanced reliability, allowing data centers to rely on a PCIe-based SSD as their primary tier one storage solution for the first time. Additionally, the Z-Drive R4's level of concentrated performance enables system architects to design more productive infrastructures while lowering operating costs associated with hard drive technology.


VCA 2.0 supports the industry standard SCSI command set and, among a litany of other things, provides highly efficient performance aggregation due to our proprietary Complex Command Queuing Structure (CCQS), that handles balancing with OCZ's unique Queue Balancing Algorithm, that extends the NAND flash life at a block level, manages redundancy, and is the software interface with the host system.

Z-Drives integrate seamlessly with servers at the system bus and kernel level, creating a new flash memory tier and dramatically increasing throughput and application performance all while slashing capital and operating costs.

### CM88 – Full Height Form Factor



### CM84 – Half Height Form Factor



PRODUCT		CAPACITY			ORDERING	
NAME	FORM FACTOR	RAW	IDEMA	WRITE ENDURANCE	PART NUMBER	UPC
Z-Drive R4 CM84	Half Height	384GB	300GB	Up to 7.5PB	ZD4CM84-HH-300G	842024027256
Z-Drive R4 CM84	Half Height	768GB	600GB	Up to 15PB	ZD4CM84-HH-600G	842024027263
Z-Drive R4 CM84	Half Height	1536GB	1200GB	Up to 30PB	ZD4CM84-HH-1.2T	842024027270
Z-Drive R4 CM88	Full Height	1024GB	800GB	Up to 20PB	ZD4CM88-FH-800G	842024027348
Z-Drive R4 CM88	Full Height	2048GB	1600GB	Up to 40PB	ZD4CM88-FH-1.6T	842024027355
Z-Drive R4 CM88	Full Height	4096GB	3200GB	Up to 80PB	ZD4CM88-FH-3.2T	842024027362

OCZ may make changes to specifications and product descriptions at any time, without notice. The information presented in this document is for informational purposes only and may contain technical inaccuracies, omissions and typographical errors. Any performance tests and ratings are measured using systems that reflect the approximate performance of OCZ products as measured by those tests. Any differences in software or hardware configuration may affect actual performance, and OCZ does not control the design or implementation of third party benchmarks or websites referenced in this document. The information contained herein is subject to change and may be rendered inaccurate for many reasons, including but not limited to any changes in product and/or roadmap, component and hardware revision changes, new model and/or product releases, software changes, firmware changes, or the like. OCZ assumes no obligation to update or otherwise correct or revise this information.

OCZ makes no representations or warranties with respect to the contents hereof and assumes no responsibility for any inaccuracies, errors or omissions that may appear in this information.

OCZ specifically disclaims any implied warranties of merchantability or fitness for any particular purpose. In no event will OCZ be liable to any person for any direct, indirect, special or other consequential damages arising from the use of any information contained herein, even if OCZ is expressly advised of the possibility of such damages.

Headquarters	Canada Corporate Office	Europe Corporate Office	Asia Pacific Corporate Office
OCZ Technology Group, Inc. 6373 San Ignacio Ave. San Jose, CA 95119 USA +1(408)733-8400 sales@occenterprise.com	160 Konrad Cres., Unit #1 Markham, Ontario L3R 9T9 +1(905)479-7976 ca_sales@occenterprise.com	Coenecoop 89B 2741 PH Waddinxveen The Netherlands +31(0)182-624020 emea_sales@occenterprise.com	16F-3, No. 700, Chung Cheng Rd. Chung Ho City, Taipei County Taiwan, 235, R.O.C. +886-2-8227-3123 apac_sales@occenterprise.com